

# Freddy Tramp Oil Separator

Leading the way in coolant recycling 



The Freddy Tramp Oil Separator has been designed to combat the problems associated with tramp oil levels in machine tool coolant systems. Tramp oil can cause a variety of problems, both to the finished product and the operator. The Tramp Oil Separator is easily manoeuvrable, so it can be used throughout the factory and it runs continuously so will not interfere with production, siphoning the tramp oil to the supplied external waste containers and returning the cleaned coolant to the machine tool sump.

- Removes tramp oil from coolants in a variety of applications
- Runs continuously
- Variety of filters and floats available
- Optional UV coolant decontaminator inhibits bacterial growth
- Complete with 24 months warranty

## Specification

- Removes tramp oil from coolants in a variety of applications
- Runs continuously
- Variety of filters and floats available
- Optional UV coolant decontaminator inhibits bacterial growth
- Complete with 24 months warranty



## Freddy Tramp Oil Separator Models

Capacity: 70 litres | Length: 800mm | Width: 516mm | Height: 1185mm

Power unit	# of phases	Weight (empty)	Weight (full)	Airflow	Water flow in *	Water flow out
240v	1	73	143	n/a	4.9 lt/min	2 lt/min
110v	1	73	143	n/a	4.9 lt/min	2 lt/min
Air	n/a	71	141	33.9	2 - 5 lt/min	2 lt/min
Air + 240v UV	1	75	145	33.9	2 - 5 lt/min	2 lt/min
Air + 110v UV	1	75	145	33.9	2 - 5 lt/min	2 lt/min

Weight in kilograms (kg)

## Optional Freddy Service agreement

All of our Freddy coolant vacuums come with a 24 month warranty and optional 12 month service agreement, which includes:

- Two service visits per year - inclusive of labour and travel
- Priority on call outs
- Reduced breakdown call out charge